IN THE CLAIMS

Please amend the claims as follows. This listing of claims replaces all prior versions and listings of claims in the application:

1. (Original) A method comprising:

determining a plurality of discrete cosine transform (DCT) coefficients based on a discrete cosine transform of a p1urality of blocks of data;

providing a first DCT-encoded signal which uses at most t coefficient bits to represent each of the DCT coefficients; and

providing a second DCT-encoded signal which uses at most u coefficient bits, wherein u is less than t, to represent each of the DCT coefficients by removing at least one lesser-significant bit from each of the DCT coefficients having t coefficient bits.

2. (Original) The method of claim 1 further comprising:

providing a third DCT-encoded signal which uses at most v coefficient bits to represent each of the DCT coefficients by removing at least two lesser-significant bits from each of the DCT coefficients having t coefficient bits;

wherein v is less than u.

- 3. (Original) The method of claim 1 wherein the first DCT-encoded signal uses t coefficient bits to represent each of the DCT coefficients, and wherein the second DCT-encoded signal uses u coefficient bits to represent each of the DCT coefficients.
- 4. (Original) The method of claim 1 wherein the first DCT-encoded signal is provided to a first data communication link having a first bandwidth, wherein the second DCT-encoded signal is provided to a second data communication link having a second bandwidth, and wherein the first bandwidth is greater than the second bandwidth.
- 5. (Original) The method of claim I wherein the first DCT-encoded signal has a first data rate, wherein the second DCT-encoded signal has a second data rate, and wherein the first data rate is greater than the second data rate.

- 6. (Original) The method of claim 1 wherein the first DCT-encoded signal and the second DCT-encoded signal are substantially synchronized.
- 7. (Original) The method of claim 1 wherein t is equal to 13 or 14.
- 8. (Original) A computer-usable medium having computer program code to direct a computer system to perform acts of:

determining a plurality of discrete cosine transform (DCT) coefficients based on a discrete cosine transform of a plurality of blocks of data;

providing a first DCT-encoded signal which uses at most t coefficient bits to represent each of the DCT coefficients; and

providing a second DCT-encoded signal which uses at most u coefficient bits, wherein u is less than t, to represent each of the DCT coefficients by removing at least one lesser-significant bit from each of the DCT coefficients having t coefficient bits.

9. (Original) The computer-usable medium of claim 8 wherein the computer program code further is to direct the computer system to perform an act of:

providing a third DCT-encoded signal which uses at most v coefficient bits to represent each of the DCT coefficients;

wherein v is less than u.

- 10. (Original) The computer-usable medium of claim 8 wherein the first DCT-encoded signal uses t coefficient bits to represent each of the DCT coefficients, and wherein the second DCT-encoded signal uses u coefficient bits to represent each of the DCT coefficients.
- 11. (Original) The computer-usable medium of claim 8 wherein the first DCT-encoded signal is provided to a first data communication link having a first bandwidth, wherein the second DCT-encoded signal is provided to a second data communication link having a second bandwidth, and wherein the first bandwidth is greater than the second bandwidth.

- 12. (Original) The computer-usable medium of claim 8 wherein the first DCT-encoded signal has a first data rate, wherein the second DCT-encoded signal has a second data rate, and wherein the first data rate is greater than the second data rate.
- 13. (Original) The computer-usable medium of claim 8 wherein the first DCT-encoded signal and the second DCT-encoded signal are substantially synchronized.
- 14. (Original) The computer-usable medium of claim 8 wherein t is equal to 13 or 14.
- 15. (Currently Amended) A system comprising:

a compression engine to determine a plurality of discrete cosine transform (DCT) coefficients based on a discrete cosine transform of a plurality of blocks of data, to provide a first DCT-encoded signal which uses at most t coefficient bits to represent each of the DCT coefficients, and to provide a second DCT-encoded signal which uses at most u coefficient bits to represent each of the DCT coefficients, wherein u is less than t, to represent each of the DCT coefficients by removing at least one lesser-significant bit from each of the DCT coefficients having t coefficient bits.

- 16. (Original) The system of claim 15 wherein the compression engine further is to provide a third DCT-encoded signal which uses at most v coefficient bits to represent each of the DCT coefficients, wherein v is less than u.
- 17. (Original) The system of claim 15 wherein the first DCT-encoded signal uses t coefficient bits to represent each of the DCT coefficients, and wherein the second DCT-encoded signal uses u coefficient bits to represent each of the DCT coefficients.
- 18. (Original) The system of claim 15 wherein the first DCT-encoded signal is provided to a first data communication link having a first bandwidth, wherein the second DCT-encoded signal is provided to a second data communication link having a second bandwidth, and wherein the first bandwidth is greater than the second bandwidth.
- 19. (Original) The system of claim 15 wherein the first DCT-encoded signal has a first data rate, wherein the second DCT-encoded signal has a second data rate, and wherein the first data rate is greater than the second data rate.

- 20. (Original) The system of claim 15 wherein the first DCT-encoded signal and the second DCT-encoded signal are substantially synchronized.
- 21. (Original) The system of claim 15 wherein t is equal to 13 or 14.
- 22. (Original) The system of claim 15 wherein the compression engine is to remove at least one lesser-significant bit from each of the DCT coefficients having t coefficient bits.